

DC-Micromotors

Graphite Commutation

131 mNm
110 W

Series 3863 ... CR

Values at 22°C and nominal voltage	3863 H	012 CR	018 CR	024 CR	036 CR	048 CR		
1 Nominal voltage	U_N		12	18	24	36	48	V
2 Terminal resistance	R		0,16	0,36	0,64	1,55	2,58	Ω
3 Output power	$P_{2nom.}$		205	211	214	201	217	W
4 Efficiency, max.	$\eta_{max.}$		83	84	85	86	86	%
5 No-load speed	n_0		5 600	5 900	5 800	5 800	5 800	min ⁻¹
6 No-load current, typ. (with shaft \varnothing 6 mm)	I_0		0,335	0,232	0,168	0,112	0,084	A
7 Stall torque	M_H		1 424	1 394	1 455	1 363	1 461	mNm
8 Friction torque	M_R		6,5	6,5	6,5	6,5	6,5	mNm
9 Speed constant	k_n		480	332	240	160	120	min ⁻¹ /V
10 Back-EMF constant	k_E		2,08	3,01	4,17	6,25	8,33	mV/min ⁻¹
11 Torque constant	k_M		19,9	28,8	39,8	59,8	79,7	mNm/A
12 Current constant	k_I		0,05	0,035	0,025	0,017	0,013	A/mNm
13 Slope of n-M curve	$\Delta n / \Delta M$		3,9	4,1	3,9	4,1	3,9	min ⁻¹ /mNm
14 Rotor inductance	L		45	90	180	400	700	μ H
15 Mechanical time constant	τ_m		4,8	4,8	4,8	4,8	4,7	ms
16 Rotor inertia	J		120	110	120	110	115	gcm ²
17 Angular acceleration	$\alpha_{max.}$		119	127	121	124	127	$\cdot 10^3$ rad/s ²
18 Thermal resistance	R_{th1} / R_{th2}	2,5 / 6						K/W
19 Thermal time constant	τ_{w1} / τ_{w2}	50 / 900						s
20 Operating temperature range:								
– motor			-30 ... +125					°C
– winding, max. permissible			+155					°C
21 Shaft bearings			ball bearings, preloaded					
22 Shaft load max.:								
– with shaft diameter			6					mm
– radial at 3 000 min ⁻¹ (3 mm from bearing)			60					N
– axial at 3 000 min ⁻¹			6					N
– axial at standstill			50					N
23 Shaft play:								
– radial	\leq		0,015					mm
– axial	$=$		0					mm
24 Housing material			steel, black coated					
25 Mass			390					g
26 Direction of rotation			clockwise, viewed from the front face					
27 Speed up to	$n_{max.}$		7 000					min ⁻¹
28 Number of pole pairs			1					
29 Magnet material			NdFeB					
Rated values for continuous operation								
30 Rated torque	M_N		69	99	129	126	131	mNm
31 Rated current (thermal limit)	I_N		4	4	4	2,6	2	A
32 Rated speed	n_N		5 430	5 660	5 510	5 500	5 550	min ⁻¹

Note: Rated values are calculated with nominal voltage and at a 22°C ambient temperature. The R_{th2} value has been reduced by 25%.

Note:

The diagram indicates the recommended speed in relation to the available torque at the output shaft for a given ambient temperature of 22°C.

The diagram shows the motor in a completely insulated as well as thermally coupled condition (R_{th2} 50% reduced).

The nominal voltage (U_N) curve shows the operating point at nominal voltage in the insulated and thermally coupled condition. Any points of operation above the curve at nominal voltage will require a higher operating voltage. Any points below the nominal voltage curve will require less voltage.



